

Presentation image. Final colour may vary.

**Ref. HE-E801**

# Two-post base-plate lift, manual release

**The essential two-post lift, 4 to 6 tonnes, with a floor plate that leaves the full height clear.**

Electro-hydraulic two-post lift for servicing and repairing cars and vans. The columns are linked by a floor plate, with no overhead beam, so the lift fits under a low ceiling. Safety locks are released by hand on each side.

## Technical specifications

| | |
|---|---|
| Lifting capacity | 4,000 to 6,000 kg |
| Lifting height | 100 to 1,850 mm |
| Lifting / lowering time | ≤ 50 s |
| Overall height | 2,800 mm |
| Drive-through width | 2,680 mm |
| Overall width | 3,250 mm |
| Safety lock release | Manual, both sides |
| Lifting arms | 2 + 3 sections, or 3 + 3 as an option |
| Motor | 2.2 kW |
| Power supply | 220 V / 380 V |
| Installation | Floor-mounted, base plate between columns |

## Key features

- Five capacities: 4,000, 4,500, 5,000, 5,500 and 6,000 kg
- 2,800 mm overall height, suits low ceilings
- Telescopic 2 + 3 section arms, 3 + 3 as an option
- Raises and lowers in 50 seconds or less
- Mechanical safety locks on each column

## How to use

- Routine servicing, oil changes and brakes
- Exhaust, driveline and running gear
- Tyres and wheels

## Packaging and delivery

| Version | Reference | |
|---|---|---|
| 4,000 kg | HE-E801-40 | Capacity 4,000 kg |
| 4,500 kg | HE-E801-45 | Capacity 4,500 kg |

| Version | Reference | |
|---|---|---|
| 5,000 kg | HE-E801-50 | Capacity 5,000 kg |
| 5,500 kg | HE-E801-55 | Capacity 5,500 kg |
| 6,000 kg | HE-E801-60 | Capacity 6,000 kg |

Package dimensions : package 1: 280 × 48 × 72 cm; package 2: 85 × 27 × 35 cm · Package weight : 500 kg (1.2 m³)

This product is available from Humming distributors. Find the one nearest to you.

**Humming Equipment** · humming-refinish.com · contact@humming-refinish.com

Humming is a brand of Maestro Équipement. All rights reserved.