

Presentation image. Final colour may vary.

Ref. HE-E802

Two-post base-plate lift, single-side release

Both columns' safety locks release from one side: fewer trips around the vehicle.

Electro-hydraulic two-post lift for servicing and repairing cars and vans. A single manual control releases the safety locks on both columns. The floor plate removes the overhead beam and the 2,800 mm column spacing leaves room to open the doors.

Technical specifications

Lifting capacity	4,000 to 5,500 kg
Lifting height	100 to 1,850 mm
Lifting / lowering time	≤ 50 s
Overall height	2,820 mm
Width between columns	2,800 mm
Overall width	3,380 mm
Safety lock release	Manual, single-side
Lifting arms	2 + 3 sections, or 3 + 3 as an option
Motor	2.2 kW
Power supply	220 V / 380 V
Installation	Floor-mounted, base plate between columns

Key features

- Three capacities: 4,000, 5,000 and 5,500 kg
- Centralised manual release from one side
- Telescopic 2 + 3 section arms, 3 + 3 as an option
- Raises and lowers in 50 seconds or less
- 2.2 kW motor, 220 V or 380 V

How to use

- Routine servicing, oil changes and brakes
- Exhaust, driveline and running gear
- Tyres and wheels

Packaging and delivery

Version	Reference	
4,000 kg	HE-E802-40	Capacity 4,000 kg

Version	Reference	
5,000 kg	HE-E802-50	Capacity 5,000 kg
5,500 kg	HE-E802-55	Capacity 5,500 kg

Package dimensions : package 1: 285 × 52 × 70 cm; package 2: 90 × 30 × 35 cm · Package weight : 610 kg (1.2 m³)

This product is available from Humming distributors. Find the one nearest to you.

Humming Equipment · humming-refinish.com · contact@humming-refinish.com

Humming is a brand of Maestro Équipement. All rights reserved.