

Presentation image. Final colour may vary.

Ref. HE-E809

In-ground alignment scissor lift, 4 t

Long-platform scissor lift set flush into the floor, for alignment and servicing.

Set into a pit, the lift is flush with the floor when lowered, so vehicles drive on without ramps. The 4,500 mm platforms take an aligner's turntables, and the built-in jacking beam frees the wheels for adjustments.

Technical specifications

Lifting capacity	4,000 kg
Lifting height	360 to 1,800 mm
Jacking beam	450 mm
Platform length	4,500 mm
Platform / overall width	600 / 2,050 mm
Lifting time	≤ 50 s
Air pressure	6 – 10 bar
Motor	2.2 kW
Power supply	220 V / 380 V
Installation	In-ground (pit-mounted)

Key features

- In-ground installation, flush with the floor
- 4,500 mm long platforms for wheel alignment
- Built-in jacking beam, 450 mm lift
- 5-tonne version available

How to use

- Wheel alignment checks and adjustment
- Routine servicing, oil changes and brakes
- Tyres and wheels

Packaging and delivery

Version	Reference	
4,000 kg – 4.5 m	HE-E809-40	Standard version
5,000 kg – 5 m	HE-E809-50	5,000 mm platforms

Package dimensions : package 1: 470 × 65 × 44 cm; package 2: 470 × 65 × 44 cm · Package weight : 1,750 kg (2.9 m³)

This product is available from Humming distributors. Find the one nearest to you.

Humming is a brand of Maestro Équipement. All rights reserved.