

Presentation image. Final colour may vary.

Ref. HE-E810

Surface-mounted ultra-thin alignment scissor lift, 4 t

Alignment scissor lift that sits on the floor, 180 mm closed, with a 2 × 2,000 kg secondary lift.

No civil works: the lift bolts straight onto the slab and stands only 180 mm high when closed. The 4,500 mm platforms are made for alignment, and the 2 × 2,000 kg secondary lift raises the wheels for adjustments.

Technical specifications

Lifting capacity	4,000 kg
Secondary lift	2 × 2,000 kg
Lifting height	180 to 1,800 mm
Jacking beam	450 mm
Platform length	4,500 mm
Platform / overall width	660 / 2,140 mm
Lifting time	≤ 50 s
Motor	2.2 kW
Power supply	220 V / 380 V
Installation	Surface-mounted, ultra-thin

Key features

- 180 mm closed height, no pit
- 4,500 mm long platforms for wheel alignment
- 2 × 2,000 kg secondary lift
- 5-tonne version available

How to use

- Wheel alignment checks and adjustment
- Routine servicing, oil changes and brakes
- Tyres and wheels

Packaging and delivery

Version	Reference	
4,000 kg – 4.5 m	HE-E810-40	Standard version
5,000 kg – 5 m	HE-E810-50	5,000 mm platforms

Package dimensions : package 1: 470 × 75 × 30 cm; package 2: 470 × 75 × 30 cm · Package weight : 1,950 kg (2.9 m³)

This product is available from Humming distributors. Find the one nearest to you.

Humming is a brand of Maestro Équipement. All rights reserved.