

Presentation image. Final colour may vary.

Ref. HE-E818

Surface-mounted ultra-thin scissor lift, 4 t

4-tonne version of the ultra-thin lift: no pit, 110 mm closed, 1,850 mm rise.

Placed directly on the slab, it avoids civil works while lifting 4 tonnes. Platforms extend from 1,450 to 2,090 mm, with pneumatic safety release.

Technical specifications

Lifting capacity	4,000 kg
Lifting height	110 to 1,850 mm
Platform length	1,450 to 2,090 mm
Platform / overall width	650 / 2,010 mm
Air pressure	0.6 to 0.8 MPa
Motor	2.2 kW
Power supply	220 V / 380 V
Installation	Surface-mounted, ultra-thin

Key features

- 110 mm closed height, no pit
- Extendable platforms to suit the wheelbase
- Pneumatic safety lock release

How to use

- Routine servicing, oil changes and brakes
- Exhaust, driveline and running gear
- Tyres and wheels

Packaging and delivery

Version	Reference
Single model	HE-E818

Package dimensions : package 1: 167.5 × 74 × 35 cm; package 2: 102 × 60 × 62.5 cm · Package weight : 890 kg (0.9 m³)

This product is available from Humming distributors. Find the one nearest to you.

Humming is a brand of Maestro Équipement. All rights reserved.